


ART. 383

Valvola di fondo in ottone.
Brass back valve.



Corpo in ottone, filtri in ottone, piattello in ottone, tenuta NBR, guarnizione in fibra, temperatura massima di esercizio 100°C.

Body in casting brass, disc in hot pressed brass seal in NBR, fiber gasket, max working temperature 100°C.

Codice - Code	Ø	PN	D	H	Conf. - Pack		€ Cad. € each
2321408	1/2"	16	38	62	15	60	5,50
2321409	3/4"	16	44	68	12	48	7,00
2321410	1"	16	48	76	6	36	8,50
2321411	1"1/4	16	57	95	5	20	13,50
2321412	1"1/2	16	66	101,5	3	12	18,00
2321413	2"	16	77	116	2	8	27,30
2321414	2"1/2	16	86	139,5	1	8	37,00
2321415	3"	16	111	148,5	1	8	58,00
2321417	4"	16	146	185	1	5	100,00

ART. 384

Valvola di fondo tubolare in ottone.
Brass tubular back valve.



Codice - Code	Ø	Conf. - Pack	€ Cad. € each
2321009	3/4"	10	12,00
2321010	1"	10	15,00
2321011	1"1/4	5	22,00
2321012	1"1/2	5	27,00
2321013	2"	2	39,00

ART. 385

Valvola di ritegno Roma.
Roma check valve.



Codice - Code	Ø	PN bar	Conf. - Pack		€ Cad. € each
2321208	1/2"	25	10	100	12,85
2321209	3/4"	25	8	72	16,10
2321210	1"	25	6	48	22,20
2321211	1"1/4	18	4	28	30,00

ART. 386

Valvola antisabbia tipo FIAT.
FIAT anti-sand valve.



Codice - Code	Ø	Conf. - Pack	€ Cad. € each
2321610	1"	1	28,40
2321611	1"1/4	1	41,20
2321612	1"1/2	1	67,00